



전선릴 CORD REEL

접지형

① MK1530



접지 차단형

② MK1530N



규격 (SQ)	코어	길이 (m)
1.5	3	28
		48
		96
1.5	3	28
		48
		96

연장선 MULTI OUTLET

① MK-108



② MK-108N



규격 (SQ)	코어	길이 (m)	IN
1.5	3	8	20
		18	15
		28	10
		48	7
1.5	3	8	20
		18	15
		28	10
		48	7

전등선 ELECTRIC LAMP WIRE



규격 (SQ)	길이 (m)	IN	구성	사용전구
1.5	10	10	망3개	베이스E26, 35W이하 삼파장
	20	5	망6개	
	25	3	망10개	
	30	3	망10개	
	50	3	망10개	
2.5	20	3	망6개	베이스E39, 55W이하 삼파장
	30	2	망10개	
	50	2	망10개	
	30	2	55W캡형, 망10개	
50	2	55W캡형, 망10개	베이스E39, 55W이하 삼파장	

멀티코드 전선릴, 작업등

투광기 받침대 LIGHT STAND

● 1등용



● 높이조절 : 1,070~1,450mm

규격	IN
1등용	2
2등용	

콘센트커버 RUBBER COVER

① 2구



② 3구



규격	IN	OUT
2구	10	90
3구		